

Product information:

Product length:	2,39 m
Product width:	5,91 m
Product height:	3,00 m
Product weight:	- kg
Execution standard:	PN-EN 1176-1:2017-12
Safety zone area:	42,54 m ²
HIC (Free fall height):	1,20 m
Suitable for inclusive users:	NO
Customisable colours:	YES
Maximum user weight:	130 kg
Suggested user age:	≤3 years
Suggested user height:	≤ 140 cm
Estimated lead time:	4 - 6 weeks



Material specification:

Main construction: Metal
 HDPE Parts: (≤ 6 mm)
 Footsteps: Nets
 Zinc primer: YES
 Painting: 2x layers of powder paint
 Screws and nuts: Stainless steel
 Montage method: -30 cm
 Standard colours: grey, yellow

Suggested safety surface:

It is necessary to construct any below safety surface to cushion falls:

- 1) Grass
- 2) Sand – fraction 0,2 to 2 mm, minimum thickness 200 mm
- 3) Gravel – fraction 2 to 8 mm, minimum thickness 200 mm
- 4) Bark – fraction 20 to 80 mm, minimum thickness 200 mm
- 5) Wood chips – fraction 5 to 30 mm, minimum thickness 200 mm
- 6) Synthetic surfaces made in compliance with the PN-EN 1177:2017 standard



Additional information:

Product colours can be adjusted
 Montage method can be adjusted
 Material of seats and footsteps can be adjusted
 Information sticker can be adjusted

Contact number: +48 730 293 393; +48 600 250 245

E-mail: info@starmax.com.pl

Factory: Poland, 83-050 Bakowo, Rycerska 3 St.

Manufacturer: Starmax Marek Starczewski

Made in Poland

